




US 9021

washer, DIN 9021

galvanized, according to ISO 4042

Артикул	Product	diameter	diameter	t	weight
US 6X18	18 mm	6.40 mm	1.60 mm	0.30 kg/100	
US 8X25	25 mm	8.40 mm	2.00 mm	0.70 kg/100	
US 10X30	30 mm	10.50 mm	2.50 mm	1.20 kg/100	
US 13X40	40 mm	13 mm	3.00 mm	2.70 kg/100	

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Артикул	Product	diameter	diameter	t	weight
US 10X30F	30 mm	10.50 mm	2.50 mm	1.20 kg/100	
US 13X40F	40 mm	13 mm	3.00 mm	2.70 kg/100	

Stainless steel, according to ASTM 304 / BS 304 S 3

Артикул	Product	diameter	diameter	t	weight
US 6X18E	18 mm	6.40 mm	1.60 mm	0.30 kg/100	
US 8X25E	25 mm	8.40 mm	2.00 mm	0.70 kg/100	
US 10X30E	30 mm	10.50 mm	2.50 mm	1.20 kg/100	

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Артикул	Product	diameter	diameter	t	weight
US 8X25E4	25 mm	8.40 mm	2.00 mm	0.70 kg/100	
US 10X30E4	30 mm	10.50 mm	2.50 mm	1.20 kg/100	

Product: Product**diameter:** diameter**diameter:** diameter**t:** material thickness**weight:** weight

