


BK 100

floor duct, perforated, height = 100 mm



Floor duct, heavy design, constructed for walk-upon use, with side perforation, including electric conductivity

Pre-embossed slugs in a distance of 100 mm enable an individual assembly e.g. a potential compensation. From a width ≥ 300 mm, use one separating strip. From a width ≥ 500 mm up, use two separating strips. Floor duct side cover on request.



Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Артикул	Product	height	width	length	t	weight
BK 100-10S	100 mm	100 mm	3000 mm	2.00 mm	15.01 kg	
BK 100-15S	100 mm	150 mm	3000 mm	2.00 mm	17.30 kg	
BK 100-20S	100 mm	200 mm	3000 mm	2.00 mm	19.66 kg	
BK 100-30S	100 mm	300 mm	3000 mm	2.00 mm	24.31 kg	
BK 100-40S	100 mm	400 mm	3000 mm	2.00 mm	29.02 kg	
BK 100-50S	100 mm	500 mm	3000 mm	2.00 mm	33.67 kg	
BK 100-60S	100 mm	600 mm	3000 mm	2.00 mm	38.31 kg	

Product: Product

height: height



width: width

length: length

t: material thickness

weight: weight

DETAILS / APPLICATIONS





ACCESSORIES

BKRKK 100, BKRKS 100, BKDR, BKD-RHP, BKDR-WZB AL, BKDR-WZB S, BKV 100, BKRT 100, BKZ, BKEB 100, BKHR, BKHC, KHZ, KSB, BKMT,



UL classified

