


BKOS 100

floor duct, not perforated, H = 100 mm



Floor duct, heavy design, constructed for walk-upon use, without side perforation, including electric conductivity

From a width ≥ 300 mm, use one separating strip. From a width ≥ 500 mm up, use two separating strips. Floor duct side cover on request.




Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Артикул	Product	height	width	length	t	weight
BKOS 100-10S	100 mm	100 mm	3000 mm	2.00 mm	14.96 kg	
BKOS 100-15S	100 mm	150 mm	3000 mm	2.00 mm	17.30 kg	
BKOS 100-20S	100 mm	200 mm	3000 mm	2.00 mm	19.61 kg	
BKOS 100-30S	100 mm	300 mm	3000 mm	2.00 mm	24.25 kg	
BKOS 100-40S	100 mm	400 mm	3000 mm	2.00 mm	28.96 kg	
BKOS 100-50S	100 mm	500 mm	3000 mm	2.00 mm	33.62 kg	
BKOS 100-60S	100 mm	600 mm	3000 mm	2.00 mm	38.26 kg	
BKOS 1.5-100-10S	100 mm	100 mm	1500 mm	2.00 mm	7.48 kg	
BKOS 1.5-100-15S	100 mm	150 mm	1500 mm	2.00 mm	8.63 kg	
BKOS 1.5-100-20S	100 mm	200 mm	1500 mm	2.00 mm	9.81 kg	
BKOS 1.5-100-30S	100 mm	300 mm	1500 mm	2.00 mm	12.13 kg	
BKOS 1.5-100-40S	100 mm	400 mm	1500 mm	2.00 mm	14.48 kg	
BKOS 1.5-100-50S	100 mm	500 mm	1500 mm	2.00 mm	16.81 kg	
BKOS 1.5-100-60S	100 mm	600 mm	1500 mm	2.00 mm	19.13 kg	
BKOS 1-100-10S	100 mm	100 mm	1000 mm	2.00 mm	4.98 kg	
BKOS 1-100-15S	100 mm	150 mm	1000 mm	2.00 mm	5.75 kg	
BKOS 1-100-20S	100 mm	200 mm	1000 mm	2.00 mm	6.54 kg	
BKOS 1-100-30S	100 mm	300 mm	1000 mm	2.00 mm	8.08 kg	
BKOS 1-100-40S	100 mm	400 mm	1000 mm	2.00 mm	9.65 kg	
BKOS 1-100-50S	100 mm	500 mm	1000 mm	2.00 mm	11.21 kg	
BKOS 1-100-60S	100 mm	600 mm	1000 mm	2.00 mm	12.75 kg	

Product: Product**height:** height**width:** width**length:** length**t:** material thickness**weight:** weight

DETAILS / APPLICATIONS



ACCESSORIES

BKRKK 100, BKRKS 100, BKDR, BKD-RHP, BKDR-WZB AL, BKDR-WZB S, BKV 100, BKRT 100, BKZ, BKEB 100, BKHR, BKHC, KHZ, KSB, BKMT,

