


BKOS 110

floor duct, not perforated, H = 110 mm



Floor duct, heavy design, constructed for walk-upon use, without side perforation, including electric conductivity

From a width ≥ 300 mm, use one separating strip. From a width ≥ 500 mm up, use two separating strips. Floor duct side cover on request.




Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Артикул	Product	height	width	length	t	weight
BKOS 110-10S	110 mm	100 mm	3000 mm	2.00 mm	15.98 kg	
BKOS 110-15S	110 mm	150 mm	3000 mm	2.00 mm	18.28 kg	
BKOS 110-20S	110 mm	200 mm	3000 mm	2.00 mm	20.63 kg	
BKOS 110-30S	110 mm	300 mm	3000 mm	2.00 mm	25.28 kg	
BKOS 110-40S	110 mm	400 mm	3000 mm	2.00 mm	29.99 kg	
BKOS 110-50S	110 mm	500 mm	3000 mm	2.00 mm	34.64 kg	
BKOS 110-60S	110 mm	600 mm	3000 mm	2.00 mm	39.28 kg	
BKOS 1.5-110-10S	110 mm	100 mm	1500 mm	2.00 mm	7.99 kg	
BKOS 1.5-110-15S	110 mm	150 mm	1500 mm	2.00 mm	9.14 kg	
BKOS 1.5-110-20S	110 mm	200 mm	1500 mm	2.00 mm	10.32 kg	
BKOS 1.5-110-30S	110 mm	300 mm	1500 mm	2.00 mm	12.64 kg	
BKOS 1.5-110-40S	110 mm	400 mm	1500 mm	2.00 mm	15 kg	
BKOS 1.5-110-50S	110 mm	500 mm	1500 mm	2.00 mm	17.32 kg	
BKOS 1.5-110-60S	110 mm	600 mm	1500 mm	2.00 mm	19.64 kg	
BKOS 1-110-10S	110 mm	100 mm	1000 mm	2.00 mm	5.33 kg	
BKOS 1-110-15S	110 mm	150 mm	1000 mm	2.00 mm	6.09 kg	
BKOS 1-110-20S	110 mm	200 mm	1000 mm	2.00 mm	6.88 kg	
BKOS 1-110-30S	110 mm	300 mm	1000 mm	2.00 mm	8.43 kg	
BKOS 1-110-40S	110 mm	400 mm	1000 mm	2.00 mm	10 kg	
BKOS 1-110-50S	110 mm	500 mm	1000 mm	2.00 mm	11.55 kg	
BKOS 1-110-60S	110 mm	600 mm	1000 mm	2.00 mm	13.09 kg	

Product: Product**height:** height**width:** width**length:** length**t:** material thickness**weight:** weight

DETAILS / APPLICATIONS



ACCESSORIES

BKRKK 110, BKRKS 110, BKDR, BKD-RHP, BKDR-WZB AL, BKDR-WZB S, BKV 110, BKRT 110, BKZ, BKEB 110, BKHR, BKHC, KHZ, KSB, BKMT,

