


BKD-RHP

floor duct cover with non-slip embossing






The cover consists of a 2 mm thick galvanized sheet steel with 1 mm non-slip embossing and slip resistance R12 according to DIN 51130. In compliance with the installation specifications and a maximum compartment size of 200 mm, the cover guarantees a tested load capacity of at least 500 kg according to EN 50085-2-2. Pre-embossed swivels in a grid of 50 mm enable individual attachment using the turning bolts DR-BK or alternatively the cover clamp BKDHK.

Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Артикул	Product	width	length	t	Pmax	weight	slip resistance class
BKD-RHP 10S	100 mm	3000 mm	2.00 mm	5 kN	6.03 kg	R12	
BKD-RHP 15S	150 mm	3000 mm	2.00 mm	5 kN	8.38 kg	R12	
BKD-RHP 20S	200 mm	3000 mm	2.00 mm	5 kN	10.74 kg	R12	
BKD-RHP 30S	300 mm	3000 mm	2.00 mm	5 kN	15.45 kg	R12	
BKD-RHP 40S	400 mm	3000 mm	2.00 mm	5 kN	20.16 kg	R12	
BKD-RHP 50S	500 mm	3000 mm	2.00 mm	5 kN	24.87 kg	R12	
BKD-RHP 60S	600 mm	3000 mm	2.00 mm	5 kN	29.58 kg	R12	
BKD-RHP 1.5-10S	100 mm	1500 mm	2.00 mm	5 kN	3.01 kg	R12	
BKD-RHP 1.5-15S	150 mm	1500 mm	2.00 mm	5 kN	4.19 kg	R12	
BKD-RHP 1.5-20S	200 mm	1500 mm	2.00 mm	5 kN	5.37 kg	R12	
BKD-RHP 1.5-30S	300 mm	1500 mm	2.00 mm	5 kN	7.72 kg	R12	
BKD-RHP 1.5-40S	400 mm	1500 mm	2.00 mm	5 kN	10.08 kg	R12	
BKD-RHP 1.5-50S	500 mm	1500 mm	2.00 mm	5 kN	12.43 kg	R12	
BKD-RHP 1.5-60S	600 mm	1500 mm	2.00 mm	5 kN	14.79 kg	R12	
BKD-RHP 1-10S	100 mm	1000 mm	2.00 mm	5 kN	2.01 kg	R12	
BKD-RHP 1-15S	150 mm	1000 mm	2.00 mm	5 kN	2.79 kg	R12	
BKD-RHP 1-20S	200 mm	1000 mm	2.00 mm	5 kN	3.58 kg	R12	
BKD-RHP 1-30S	300 mm	1000 mm	2.00 mm	5 kN	5.15 kg	R12	
BKD-RHP 1-40S	400 mm	1000 mm	2.00 mm	5 kN	6.72 kg	R12	
BKD-RHP 1-50S	500 mm	1000 mm	2.00 mm	5 kN	8.29 kg	R12	
BKD-RHP 1-60S	600 mm	1000 mm	2.00 mm	5 kN	9.86 kg	R12	

Product: Product**width:** width**length:** length**t:** material thickness**Pmax:** Maximum load**weight:** weight**slip resistance class:** slip resistance according to DIN 51130

DETAILS / APPLICATIONS



ACCESSORIES

BKDSL, BKDHK, BKDH, DR-BK, BKDU 100, BKDU 110,

