


BKDR-WZB S

floor duct cover with aluminium chequered plate




The cover consists of a 2 mm thick galvanized sheet steel with an aluminum sheet support with non-slip embossing and slip resistance R10 according to DIN 51130. In compliance with the installation specifications and a maximum compartment size of 200 mm, the cover guarantees a tested load capacity of at least 500 kg according to EN 50085-2-2.

Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Артикул	Product	width	length	t	Pmax	weight	slip resistance class
BKDR-WZB 10S	100 mm	3000 mm	2.00 mm	5 kN	7.36 kg	R10	
BKDR-WZB 15S	150 mm	3000 mm	2.00 mm	5 kN	10.28 kg	R10	
BKDR-WZB 20S	200 mm	3000 mm	2.00 mm	5 kN	13.36 kg	R10	
BKDR-WZB 30S	300 mm	3000 mm	2.00 mm	5 kN	19.32 kg	R10	
BKDR-WZB 40S	400 mm	3000 mm	2.00 mm	5 kN	25.30 kg	R10	
BKDR-WZB 50S	500 mm	3000 mm	2.00 mm	5 kN	31.28 kg	R10	
BKDR-WZB 60S	600 mm	3000 mm	2.00 mm	5 kN	37.26 kg	R10	
BKDR-WZB 1.5-10S	100 mm	1500 mm	2.00 mm	5 kN	3.66 kg	R10	
BKDR-WZB 1.5-15S	150 mm	1500 mm	2.00 mm	5 kN	5.22 kg	R10	
BKDR-WZB 1.5-20S	200 mm	1500 mm	2.00 mm	5 kN	6.66 kg	R10	
BKDR-WZB 1.5-30S	300 mm	1500 mm	2.00 mm	5 kN	9.64 kg	R10	
BKDR-WZB 1.5-40S	400 mm	1500 mm	2.00 mm	5 kN	12.63 kg	R10	
BKDR-WZB 1.5-50S	500 mm	1500 mm	2.00 mm	5 kN	15.63 kg	R10	
BKDR-WZB 1.5-60S	600 mm	1500 mm	2.00 mm	5 kN	18.62 kg	R10	
BKDR-WZB 1-10S	100 mm	1000 mm	2.00 mm	5 kN	2.47 kg	R10	
BKDR-WZB 1-15S	150 mm	1000 mm	2.00 mm	5 kN	3.51 kg	R10	
BKDR-WZB 1-20S	200 mm	1000 mm	2.00 mm	5 kN	4.47 kg	R10	
BKDR-WZB 1-30S	300 mm	1000 mm	2.00 mm	5 kN	6.46 kg	R10	
BKDR-WZB 1-40S	400 mm	1000 mm	2.00 mm	5 kN	8.45 kg	R10	
BKDR-WZB 1-50S	500 mm	1000 mm	2.00 mm	5 kN	10.44 kg	R10	
BKDR-WZB 1-60S	600 mm	1000 mm	2.00 mm	5 kN	12.43 kg	R10	

Product: Product**width:** width**length:** length**t:** material thickness**Pmax:** Maximum load**weight:** weight**slip resistance class:** slip resistance according to DIN 51130

DETAILS / APPLICATIONS



ACCESSORIES

BKDSL, DR-BK, BKDU 100, BKDU 110,

