


BKDR

floor duct cover with turning bolts



In compliance with the installation specifications and a maximum compartment size of 200 mm, the cover guarantees a tested load capacity of at least 500 kg according to EN 50085-2-2.

Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Артикул	Product	width	length	t	Pmax	weight
BKDR 10S	100 mm	3000 mm	2.00 mm	5 kN	6.08 kg	
BKDR 15S	150 mm	3000 mm	2.00 mm	5 kN	8.56 kg	
BKDR 20S	200 mm	3000 mm	2.00 mm	5 kN	10.80 kg	
BKDR 30S	300 mm	3000 mm	2.00 mm	5 kN	15.50 kg	
BKDR 40S	400 mm	3000 mm	2.00 mm	5 kN	20.21 kg	
BKDR 50S	500 mm	3000 mm	2.00 mm	5 kN	24.92 kg	
BKDR 60S	600 mm	3000 mm	2.00 mm	5 kN	29.63 kg	
BKDR 1.5-10S	100 mm	1500 mm	2.00 mm	5 kN	3.09 kg	
BKDR 1.5-15S	150 mm	1500 mm	2.00 mm	5 kN	4.27 kg	
BKDR 1.5-20S	200 mm	1500 mm	2.00 mm	5 kN	5.45 kg	
BKDR 1.5-30S	300 mm	1500 mm	2.00 mm	5 kN	7.80 kg	
BKDR 1.5-40S	400 mm	1500 mm	2.00 mm	5 kN	10.16 kg	
BKDR 1.5-50S	500 mm	1500 mm	2.00 mm	5 kN	12.51 kg	
BKDR 1.5-60S	600 mm	1500 mm	2.00 mm	5 kN	14.87 kg	
BKDR 1-10S	100 mm	1000 mm	2.00 mm	5 kN	2.09 kg	
BKDR 1-15S	150 mm	1000 mm	2.00 mm	5 kN	2.87 kg	
BKDR 1-20S	200 mm	1000 mm	2.00 mm	5 kN	3.66 kg	
BKDR 1-30S	300 mm	1000 mm	2.00 mm	5 kN	5.23 kg	
BKDR 1-40S	400 mm	1000 mm	2.00 mm	5 kN	6.80 kg	
BKDR 1-50S	500 mm	1000 mm	2.00 mm	5 kN	8.37 kg	
BKDR 1-60S	600 mm	1000 mm	2.00 mm	5 kN	9.94 kg	

Product: Product

width: width


length: length

t: material thickness

Pmax: Maximum load

weight: weight

DETAILS / APPLICATIONS



ACCESSORIES

BKDSL, DR-BK, BKDU 100, BKDU 110,

