


## BKGLDR

floor duct cover, left with mitre cut and turning bolts



In compliance with the installation specifications and a maximum compartment size of 200 mm, the cover guarantees a tested load capacity of at least 500 kg according to EN 50085-2-2.

Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

| Артикул    | Product | width   | t    | Pmax    | weight |
|------------|---------|---------|------|---------|--------|
| BKGLDR 10S | 100 mm  | 2.00 mm | 5 kN | 0.63 kg |        |
| BKGLDR 15S | 150 mm  | 2.00 mm | 5 kN | 0.93 kg |        |
| BKGLDR 20S | 200 mm  | 2.00 mm | 5 kN | 1.25 kg |        |
| BKGLDR 30S | 300 mm  | 2.00 mm | 5 kN | 2.05 kg |        |
| BKGLDR 40S | 400 mm  | 2.00 mm | 5 kN | 2.99 kg |        |
| BKGLDR 50S | 500 mm  | 2.00 mm | 5 kN | 4.09 kg |        |
| BKGLDR 60S | 600 mm  | 2.00 mm | 5 kN | 5.35 kg |        |

**Product:** Product


**width:** width

**t:** material thickness

**Pmax:** Maximum load

**weight:** weight

## DETAILS / APPLICATIONS





## ACCESSORIES

DR-BK, BKDU 100, BKDU 110,

