


BKSDR-RHP

floor duct riser bend cover with non-slip embossing



Cover with non-slip embossing and turning bolts for floor duct riser bend.

The cover consists of a 2 mm thick galvanized sheet steel with 1 mm non-slip embossing and slip resistance R12 according to DIN 51130. In compliance with the installation specifications and a maximum compartment size of 200 mm, the cover guarantees a tested load capacity of at least 500 kg according to EN 50085-2-2.

Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Артикул	Product	height	width	length	t	Pmax	weight	slip resistance class
BKSDR-RHP 10S	200 mm	100 mm	200 mm	2.00 mm	5 kN	0.76 kg	R12	
BKSDR-RHP 15S	200 mm	150 mm	200 mm	2.00 mm	5 kN	1.02 kg	R12	
BKSDR-RHP 20S	200 mm	200 mm	200 mm	2.00 mm	5 kN	1.29 kg	R12	
BKSDR-RHP 30S	200 mm	300 mm	200 mm	2.00 mm	5 kN	1.82 kg	R12	
BKSDR-RHP 40S	200 mm	400 mm	200 mm	2.00 mm	5 kN	2.35 kg	R12	
BKSDR-RHP 50S	200 mm	500 mm	200 mm	2.00 mm	5 kN	2.88 kg	R12	
BKSDR-RHP 60S	200 mm	600 mm	200 mm	2.00 mm	5 kN	3.41 kg	R12	

Product: Product

height: height

width: width

length: length


t: material thickness

Pmax: Maximum load

weight: weight

slip resistance class: slip resistance according to DIN 51130

DETAILS / APPLICATIONS





ACCESSORIES

BKS 100, BKS 110,

