


ВКАА 100

floor duct attachment branch, height = 100 mm



From a width ≥ 300 mm, one separating strip must be installed. From a width of ≥ 500 mm, two separating strips must be installed.



Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Артикул	Product	height	width	t	weight	incl.
ВКАА 100-10S	100 mm	100 mm	2.00 mm	1.31 kg	show all inclusive accessoires	
ВКАА 100-15S	100 mm	150 mm	2.00 mm	1.46 kg	show all inclusive accessoires	
ВКАА 100-20S	100 mm	200 mm	2.00 mm	1.54 kg	show all inclusive accessoires	
ВКАА 100-30S	100 mm	300 mm	2.00 mm	1.76 kg	show all inclusive accessoires	
ВКАА 100-40S	100 mm	400 mm	2.00 mm	1.97 kg	show all inclusive accessoires	
ВКАА 100-50S	100 mm	500 mm	2.00 mm	2.19 kg	show all inclusive accessoires	
ВКАА 100-60S	100 mm	600 mm	2.00 mm	2.41 kg	show all inclusive accessoires	

Product: Product

height: height


width: width

t: material thickness

weight: weight

incl.: incl.

DETAILS / APPLICATIONS





ACCESSORIES

BKAADR, BKAADR-RHP, BKAADR-WZB AL, BKAADR-WZB S, BKRTV 100, BKDS 100,



UL classified

