




GID

mesh cable tray cover

Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Артикул	Product	width	length	weight
GID 06S	60 mm	3000 mm	3.53 kg	
GID 12S	120 mm	3000 mm	4.71 kg	
GID 20S	200 mm	3000 mm	7.07 kg	
GID 30S	300 mm	3000 mm	9.42 kg	
GID 40S	400 mm	3000 mm	11.78 kg	
GID 50S	500 mm	3000 mm	14.13 kg	
GID 60S	600 mm	3000 mm	20.61 kg	

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Артикул	Product	width	length	weight
GID 06F	60 mm	3000 mm	3.47 kg	
GID 12F	120 mm	3000 mm	4.99 kg	
GID 20F	200 mm	3000 mm	7.00 kg	
GID 30F	300 mm	3000 mm	9.53 kg	
GID 40F	400 mm	3000 mm	12.09 kg	
GID 50F	500 mm	3000 mm	14.57 kg	
GID 60F	600 mm	3000 mm	21.05 kg	

Stainless steel, according to ASTM 304 / BS 304 S 3

Артикул	Product	width	length	weight
GID 06E	60 mm	3000 mm	3.56 kg	
GID 12E	120 mm	3000 mm	4.74 kg	
GID 20E	200 mm	3000 mm	7.11 kg	
GID 30E	300 mm	3000 mm	9.48 kg	
GID 40E	400 mm	3000 mm	11.85 kg	
GID 50E	500 mm	3000 mm	14.22 kg	
GID 60E	600 mm	3000 mm	20.74 kg	

Product: Product

width: width

length: length

weight: weight

DETAILS / APPLICATIONS

