




GIDR

mesh cable tray cover with turning bolts

Installation of covers in outdoor areas requires additional provisions against storm forces. Turning bolts are in no case sufficient as security provision.

Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Артикул	Product	width	length	weight
GIDR 06S	100 mm	3000 mm	3.31 kg	
GIDR 12S	100 mm	3000 mm	4.73 kg	
GIDR 20S	200 mm	3000 mm	6.61 kg	
GIDR 30S	300 mm	3000 mm	8.97 kg	
GIDR 40S	400 mm	3000 mm	11.26 kg	
GIDR 50S	500 mm	3000 mm	13.69 kg	
GIDR 60S	600 mm	3000 mm	20.08 kg	

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Артикул	Product	width	length	weight
GIDR 06F	100 mm	3000 mm	3.53 kg	
GIDR 12F	100 mm	3000 mm	5.05 kg	
GIDR 20F	200 mm	3000 mm	7.07 kg	
GIDR 30F	300 mm	3000 mm	9.53 kg	
GIDR 40F	400 mm	3000 mm	12.12 kg	
GIDR 50F	500 mm	3000 mm	14.64 kg	
GIDR 60F	600 mm	3000 mm	21.49 kg	

Stainless steel, according to ASTM 304 / BS 304 S 3

Артикул	Product	width	length	weight
GIDR 06E	100 mm	3000 mm	3.33 kg	
GIDR 12E	100 mm	3000 mm	4.75 kg	
GIDR 20E	200 mm	3000 mm	6.65 kg	
GIDR 30E	300 mm	3000 mm	9.03 kg	
GIDR 40E	400 mm	3000 mm	11.40 kg	
GIDR 50E	500 mm	3000 mm	13.77 kg	
GIDR 60E	600 mm	3000 mm	20.22 kg	

Product: Product

width: width

length: length

weight: weight

DETAILS / APPLICATIONS

