



KHU 57

bracket support, 57x30mm

Bracket support, U-profile 57x30x2.5 mm, continuously three-way perforated.

Higher loads can be achieved by using the support piece.

galvanized, according to ISO 4042

Артикул	Product	height	width	length	weight
KHU 57-30GV	30 mm	57 mm	3000 mm	5.09 kg	

Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Артикул	Product	height	width	length	weight
KHU 57-02S	30 mm	57 mm	200 mm	0.34 kg	
KHU 57-03S	30 mm	57 mm	300 mm	0.51 kg	
KHU 57-04S	30 mm	57 mm	400 mm	0.68 kg	
KHU 57-05S	30 mm	57 mm	500 mm	0.85 kg	
KHU 57-06S	30 mm	57 mm	600 mm	1.02 kg	
KHU 57-07S	30 mm	57 mm	700 mm	1.19 kg	
KHU 57-08S	30 mm	57 mm	800 mm	1.36 kg	
KHU 57-09S	30 mm	57 mm	900 mm	1.53 kg	
KHU 57-10S	30 mm	57 mm	1000 mm	1.70 kg	
KHU 57-11S	30 mm	57 mm	1100 mm	1.87 kg	
KHU 57-12S	30 mm	57 mm	1200 mm	2.04 kg	
KHU 57-13S	30 mm	57 mm	1300 mm	2.21 kg	
KHU 57-14S	30 mm	57 mm	1400 mm	2.38 kg	
KHU 57-15S	30 mm	57 mm	1500 mm	2.55 kg	
KHU 57-30S	30 mm	57 mm	3000 mm	5.09 kg	
KHU 57-60S	30 mm	57 mm	6000 mm	10.18 kg	

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Артикул	Product	height	width	length	weight
KHU 57-02F	30 mm	57 mm	200 mm	0.36 kg	
KHU 57-03F	30 mm	57 mm	300 mm	0.55 kg	
KHU 57-04F	30 mm	57 mm	400 mm	0.73 kg	
KHU 57-05F	30 mm	57 mm	500 mm	0.91 kg	

Артикул	Product	height	width	length	weight
KHU 57-06F	30 mm	57 mm	600 mm	1.09 kg	
KHU 57-07F	30 mm	57 mm	700 mm	1.27 kg	
KHU 57-08F	30 mm	57 mm	800 mm	1.45 kg	
KHU 57-09F	30 mm	57 mm	900 mm	1.63 kg	
KHU 57-10F	30 mm	57 mm	1000 mm	1.82 kg	
KHU 57-11F	30 mm	57 mm	1100 mm	2.00 kg	
KHU 57-12F	30 mm	57 mm	1200 mm	2.18 kg	
KHU 57-13F	30 mm	57 mm	1300 mm	2.36 kg	
KHU 57-14F	30 mm	57 mm	1400 mm	2.54 kg	
KHU 57-15F	30 mm	57 mm	1500 mm	2.72 kg	
KHU 57-30F	30 mm	57 mm	3000 mm	5.45 kg	
KHU 57-60F	30 mm	57 mm	6000 mm	10.89 kg	

Stainless steel, according to ASTM 304 / BS 304 S 3

Артикул	Product	height	width	length	weight
KHU 57-02E	30 mm	57 mm	200 mm	0.34 kg	
KHU 57-03E	30 mm	57 mm	300 mm	0.51 kg	
KHU 57-04E	30 mm	57 mm	400 mm	0.68 kg	
KHU 57-05E	30 mm	57 mm	500 mm	0.85 kg	
KHU 57-06E	30 mm	57 mm	600 mm	1.03 kg	
KHU 57-07E	30 mm	57 mm	700 mm	1.20 kg	
KHU 57-08E	30 mm	57 mm	800 mm	1.37 kg	
KHU 57-09E	30 mm	57 mm	900 mm	1.54 kg	
KHU 57-10E	30 mm	57 mm	1000 mm	1.71 kg	
KHU 57-11E	30 mm	57 mm	1100 mm	1.88 kg	
KHU 57-12E	30 mm	57 mm	1200 mm	2.05 kg	
KHU 57-13E	30 mm	57 mm	1300 mm	2.22 kg	
KHU 57-14E	30 mm	57 mm	1400 mm	2.39 kg	
KHU 57-15E	30 mm	57 mm	1500 mm	2.56 kg	
KHU 57-30E	30 mm	57 mm	3000 mm	5.12 kg	
KHU 57-60E	30 mm	57 mm	6000 mm	10.25 kg	

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Артикул	Product	height	width	length	weight
KHU 57-02E4	30 mm	57 mm	200 mm	0.35 kg	
KHU 57-03E4	30 mm	57 mm	300 mm	0.52 kg	
KHU 57-04E4	30 mm	57 mm	400 mm	0.69 kg	
KHU 57-05E4	30 mm	57 mm	500 mm	0.87 kg	
KHU 57-06E4	30 mm	57 mm	600 mm	1.04 kg	
KHU 57-07E4	30 mm	57 mm	700 mm	1.21 kg	
KHU 57-08E4	30 mm	57 mm	800 mm	1.38 kg	
KHU 57-09E4	30 mm	57 mm	900 mm	1.56 kg	

Артикул	Product	height	width	length	weight
KHU 57-10E4	30 mm	57 mm	1000 mm	1.73 kg	
KHU 57-11E4	30 mm	57 mm	1100 mm	1.90 kg	
KHU 57-12E4	30 mm	57 mm	1200 mm	2.08 kg	
KHU 57-13E4	30 mm	57 mm	1300 mm	2.25 kg	
KHU 57-14E4	30 mm	57 mm	1400 mm	2.42 kg	
KHU 57-15E4	30 mm	57 mm	1500 mm	2.59 kg	
KHU 57-30E4	30 mm	57 mm	3000 mm	5.19 kg	
KHU 57-60E4	30 mm	57 mm	6000 mm	10.38 kg	

Product: Product




height: height

width: width


length: length

weight: weight

DETAILS / APPLICATIONS



$$\begin{aligned}
 A &= 1.92 \text{ cm}^2 \\
 W_y &= 3.33 \text{ cm}^3 \\
 W_z &= 0.90 \text{ cm}^3 \\
 I_y &= 9.50 \text{ cm}^4 \\
 I_z &= 1.97 \text{ cm}^4
 \end{aligned}$$



$$\begin{aligned}
 A &= 1.92 \text{ cm}^2 \\
 W_y &= 3.33 \text{ cm}^3 \\
 W_z &= 0.90 \text{ cm}^3 \\
 I_y &= 9.50 \text{ cm}^4 \\
 I_z &= 1.97 \text{ cm}^4
 \end{aligned}$$

ACCESSORIES

KWF, KW, KWMS, KDU 57, BGU 57, BGUD, BGUDW, KHUV 57, KHUSS 57, SU 57,

