


WPDUK

cover clamp



Cover clamp with screw head for mounting wide span covers on the underside for a flat appearance.

Can also be used as storm protection angle. According to assembly instructions you should use at least 6 safety elements for each 3 meters cable path cover. For wind-exposed areas, the number of cover clamps must be increased to at least 10 pcs.

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Артикул	Product	height	width	length	t	torque	weight	incl.
WPDUK F	22 mm	20 mm	21 mm	3.00 mm	2 Nm	0.02 kg	show all inclusive accessoires	

Stainless steel, according to ASTM 304 / BS 304 S 3

Артикул	Product	height	width	length	t	torque	weight	incl.
WPDUK E	22 mm	20 mm	21 mm	3.00 mm	2 Nm	0.02 kg	show all inclusive accessoires	

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Артикул	Product	height	width	length	t	torque	weight	incl.
WPDUK E4	22 mm	20 mm	21 mm	3.00 mm	2 Nm	0.02 kg	show all inclusive accessoires	

Product: Product

height: height

width: width

length: length

t: material thickness

torque: torque

weight: weight

incl.: incl.

DETAILS / APPLICATIONS

