


## WPDUK

### cover clamp



Cover clamp with screw head for mounting wide span covers on the underside for a flat appearance.

Can also be used as storm protection angle. According to assembly instructions you should use at least 6 safety elements for each 3 meters cable path cover. For wind-exposed areas, the number of cover clamps must be increased to at least 10 pcs.

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

| Артикул | Product | height | width | length  | t    | torque  | weight                         | incl. |
|---------|---------|--------|-------|---------|------|---------|--------------------------------|-------|
| WPDUK F | 22 mm   | 20 mm  | 21 mm | 3.00 mm | 2 Nm | 0.02 kg | show all inclusive accessoires |       |

Stainless steel, according to ASTM 304 / BS 304 S 3

| Артикул | Product | height | width | length  | t    | torque  | weight                         | incl. |
|---------|---------|--------|-------|---------|------|---------|--------------------------------|-------|
| WPDUK E | 22 mm   | 20 mm  | 21 mm | 3.00 mm | 2 Nm | 0.02 kg | show all inclusive accessoires |       |

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

| Артикул  | Product | height | width | length  | t    | torque  | weight                         | incl. |
|----------|---------|--------|-------|---------|------|---------|--------------------------------|-------|
| WPDUK E4 | 22 mm   | 20 mm  | 21 mm | 3.00 mm | 2 Nm | 0.02 kg | show all inclusive accessoires |       |

**Product:** Product

**height:** height

**width:** width

**length:** length

**t:** material thickness

**torque:** torque

**weight:** weight

**incl.:** incl.

## DETAILS / APPLICATIONS

